

MATERIAL SAFETY DATA SHEET



Komplek Pergudangan Bizhub Serpong GB.15
Jl. Raya Puspitek - Gn. Sindur, Bogor
Tlp : 021- 758 76 888
Fax : 021- 758 73 111

PRODUCT NAME : REVITALIZER DRY BLACK

PHYSICAL DESCRIPTION / PROPERTIES :

Black liquid ; SG : 1,1 ; pH: 2,45

HAZARDOUS INGREDIENTS ;

| CHEMICAL ENTITY : | PROPORTION : |
|-------------------|--------------|
| Silica | 13 % |
| FEVE | 3,8 % |
| Oxalic Acid | 2.2 % |
| Water | 8,1 % |

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Irritate the eyes and the skin.

FIRST AID :

Contact with skin :

Wash immediately with plenty of water for about 15 minutes. Consult with doctor immediately.

Contact with eyes :

Rinse immediately with plenty of water at least for 15 minutes. Consult with doctor immediately.

Inhalation:

Move the patient to fresh air. If he has irregular and discontinued breathing, consult with doctor.

Ingestion:

Induce the patient vomit only if instructed. Consult with doctor immediately. Do not give any medicine through way of mouth if the patient is unconscious and if not authorized by doctor.

REVITALIZER DRY BLACK

ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIONS :

Wear gloves and protective clothing.

ENVIRONMENTAL PRECAUTIONS:

Extinguish the sources of lighting or heat; cover the leaking absorbing material; pick up the flowed material and get rid of the remaining products with jets of water.

For more information regarding the environmental and the health risks, the breathing tract protection, the ventilation and the individual means of protection, see other sections of this sheet.

SPREADING INTO WATER:

Remove the product from the surface with a non-burning pomp either manual or with suitable absorbing material. If legally allowed, in open water you can resort to the sinking and/or to the dispelling of the product with suitable substances.

METHODS FOR CLEANING UP:

If in liquid form, prevent from flowing into drainage system. Pick the product to reuse, if possible, or for elimination. Eventually, absorbing with inert material. After picking, wash the area and materials involved.

FLAMMABILITY :

Non—flammable.

EXPOSURE LIMITS :

N A

SAFE HANDLING INFORMATION

ADVICE ON HANDLING:

Avoid contact and inhalation of vapor. See also next paragraph 8. During work, do not eat or drink. For more information on the environmental and health risks, let alone on the individual means of protection, see other sections of this sheet.

STORAGE CONDITIONS:

Keep in dry and ventilated rooms. Ensure good ventilation and change of air in the working area. Keep always containers closed when not used.

REQUIREMENTS FOR STORAGE ROOMS:

Appropriate aired.