

MATERIAL SAFETY DATA SHEET



Komplek Industri Taman Tekno Blok H 2 No. 22 – BSD City
Tangerang – Banten 15314
Tlp : 021- 758 76 888
Fax : 021- 758 73 111

PRODUCT NAME : LX NEUTRAL PLUS

U.N Number : 1805

DANGEROUS GOODS CLASS : 8

PHYSICAL DESCRIPTION / PROPERTIES :

Clear liquid ; SG : 1.05 ; pH : 1.0 – 2.0

HAZARDOUS INGREDIENTS ;

CHEMICAL ENTITY :

PROPORTION :

Phosphoric acid

1 – 10 %

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Swallowed : Harmful or fatal causes chemical burning of mouth, throat and stomach.

Inhaled : Cause severe chemical burn on respiratory system.

Eyes : Cause severe chemical burn and intense irritation and can result in loss of sight.

Skin : Cause severe chemical blindness

First Aid :

Swallowed : Do not induce vomiting. Rinse mouth ; then drink 1 or 2 large glasses of water or milk . Never give anything by mouth to an unconscious person.

Inhaled : Remove to fresh air

Skin : Flush immediately with large amount of water.

Eyes : Flush thoroughly with water for several minutes. Remove contact lenses

LX NEUTRAL PLUS

PRECAUTIONS FOR USE

PERSONAL PROTECTIONS :
GOGGLES, RUBBER GLOVES ARE MINIMUM
REQUIREMENT.

VENTILATION :
ADEQUATE VENTILATION IS EXPECTED TO BE
SUFFICIENT.

FLAMMABILITY :
NON—FLAMMABLE.

EXPOSURE LIMITS :
TLV = 1 MG/M³

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT :

This product is stable at room temperature if store in closed containers. Store this product in HDPE or polyethylene lined drums. Away from heat sources and sunlight.

SPILL AND DISPOSAL :

Rinse small amount to drain where possible. Unused product is RCRA Corrosive (D002)

FIRE / EXPLOSION HAZARD :

NA

OTHER :

NA