MATERIAL SAFETY DATA SHEET



Komplek Industri Taman Tekno Blok H 2 No. 22 – BSD City

Tangerang – Banten 15314

Tlp: 021-758 76 888 Fax: 021-758 73 111

PRODUCT NAME : GREEZAWAY NC

U.N Number : 1903

DANGEROUS GOODS CLASS: 8

PHYSICAL DESCRIPTION / PROPERTIES:

Brown liquid; odour: No Fragrance; SG: 0.98 – 1.0; pH: 10 (100 %)

HAZARDOUS INGREDIENTS

CHEMICAL IDENTITY: PROPORTION:

Nonylphenol Ethoxylate - 10 3 % Alkoxylated QAC & FAEO 12 %

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Inhalation: Harmful if inhaled
Ingestion: Harmful if swallowed

Swallowed: May cause stomach distress, nausea or vomiting.

Eyes & Skin: May cause irritation.

First Aid:

Swallowed : Call a poison control center or doctor immediately for treatment

advice.

Inhaled: Move person to fresh air.

Skin: Take off Contaminated Clothing.

Eyes: Hold eye and rinse slowly and gently with water for 15 - 20 minutes.

GREEZAWAY NC

PRECAUTIONS FOR USE

PERSONAL PROTECTIONS:

GOGGLES, PVC OR RUBBER GLOVESARE MINIMUM REQUIREMENT.

VENTILATION:

LOCAL EXHAUST

FLAMMABILITY:

NON-FLAMMABLE.

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT:

This product is stable at room temperature if store in closed containers. Store this product in HDPE or polyethylene lined drums. Away from heat sources and sunlight

FIRE / EXPLOSION HAZARD:

Explosive mixtures can form with air. Combustion products are toxic. Solvents can travel to an ignition source and flash back.

OTHER:

Keep out of reach of children. Do not breathe spray mist.