

MATERIAL SAFETY DATA SHEET



Komplek Industri Taman Tekno Blok H 2 No. 22 – BSD City
Tangerang – Banten 15314
Tlp : 021- 758 76 888
Fax : 021- 758 73 111

PRODUCT NAME : LX DETERGENT PRIMA

U.N Number : 2810

DANGEROUS GOODS CLASS : 6.1

PHYSICAL DESCRIPTION / PROPERTIES :

Clear Liquid ; SG : 1,01-1,04 ; pH : 6 (100%)

HAZARDOUS INGREDIENTS ;

CHEMICAL ENTITY :	PROPORTION (%) :
Anti Redeposition agent	6
Non Ionic Surfactant	8

HEALTH HAZARD INFORMATION

HEALTH EFFECTS :

Inhalation : Cause irritation to the respiratory tract.

Ingestion : Cause irritation to the gastrointestinal tract.

Skin : May cause irritation with redness and pain. May be absorbed through the skin with possible systemic effects.

Eye Contact : Vapors are irritating and may produce immediate pain, redness and tearing.

First Aid :

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen.

Ingestion : Induce vomiting immediately as directed by medical personnel.

Skin Contact : Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Eyes : Immediately flush eyes with gentle but large stream of water for at least 15 minutes, lifting lower and upper eyelids occasionally.

LX DETERGENT PRIMA

PRECAUTIONS FOR USE

PERSONAL PROTECTIONS :

GOGGLES & SHIELD, LAB COAT & APRON ; VENT HOOD
; PROPER GLOVES

VENTILATION :

A SYSTEM OF LOCAL AND/OR GENERAL EXHAUST.

FLAMMABILITY :

FLAMMABLE .

EXPOSURE LIMITS :

OSHA PERMISSIBLE EXPOSURE LIMIT : 50 ppm SKIN

ACGIH THRESHOLD LIMIT VALUE : 20 ppm (TWA)

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT :

Protect against physical damage. Store in cool, dry well-ventilated location, away from any area where the fire hazard may be acute.

SPILL AND DISPOSAL :

State and local disposal regulations may differ from federal disposal regulations.

FIRE / EXPLOSION HAZARD :

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surface to distant ignition source and flash back. Contact with strong oxidizers may cause fire. Sensitive to static discharge.

OTHER :

N/A