

MATERIAL SAFETY DATA SHEET



Komplek Industri Taman Tekno Blok H 2 No. 22 – BSD City
Tangerang – Banten 15314
Tlp : 021- 758 76 888
Fax : 021- 758 73 111

PRODUCT NAME : LX NEUTRAL

U.N Number : 1824

DANGEROUS GOODS CLASS : 8

PHYSICAL DESCRIPTION / PROPERTIES :

Clear Liquid ; pH : 1,0

HAZARDOUS INGREDIENTS ;

CHEMICAL ENTITY :	PROPORTION (%) :
Phosporic Acid	85

HEALTH HAZARD INFORMATION

HEALTH EFFECTS :

Swallowed : Harmful or fatal causes chemical burning of mouth, throat and stomach.

Inhaled : Cause severe chemical burn on respiratory system

Eyes : Cause severe chemical burn and intense irritation and can result in loss of sight.

Skin : Cause severe chemical burn.

First Aid :

Swallowed : Do not induce vomiting. Rinse mouth ; then drink 1 or 2 large glasses of water or milk . Never give anything by mouth to an unconscious person.

Inhaled : Remove to fresh air

Skin : Flush immediately with large amount of water.

Eyes : Flush thoroughly with water for several minutes. Remove contact lenses

LX NEUTRAL

PRECAUTIONS FOR USE

PERSONAL PROTECTIONS :
GOOGLES,PVC OR RUBBER GLOVES ARE MINIMUM REQUIREMENT.

VENTILATION :
ADEQUATE VENTILATION IS EXPECTED TO BE SUFFICIENT.

FLAMMABILITY :

NON—FLAMMABLE .

EXPOSURE LIMITS :

TLV = 1MG/M³

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT :

This product is stable at room temperature if store in closed containers. Store this product in HDPE or polyethylene lined drums. Away from heat sources and sunlight.

SPILL AND DISPOSAL :

Rinse small amount to drain where possible. Unused product is RCRA Corrosive (D002)

FIRE / EXPLOSION HAZARD :

Not established.

OTHER :

NA