MATERIAL SAFETY DATA SHEET



Komplek Industri Taman Tekno Blok H 2 No. 22 – BSD City

Tangerang – Banten 15314 Tlp: 021-758 76 888

Fax: 021-758 73 111

PRODUCT NAME: LX SOFT X-TRA

U.N Number: NA

DANGEROUS GOODS CLASS: NA

PHYSICAL DESCRIPTION / PROPERTIES:

Blue liquid; SG: 1.01; pH: 6.5 - 7.0 (100 %)

HAZARDOUS INGREDIENTS;

CHEMICAL ENTITY: PROPORTION:

NA NA

HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Swallowed: May causes stomach distress, nausea or vomiting.

Inhaled: Cause severe chemical burn on respiratory system.

Eyes: Cause minor to moderate irritation.

Skin: Cause minor to moderate irritation.

First Aid:

Swallowed: Do not induce vomiting. Rinse mouth; then drink 1 or 2 large glasses of water or milk. Never give anything by mouth to an unconscious person.

Inhaled: Remove to fresh air

Skin: Flush immediately with large amount of water.

Eyes: Flush thoroughly with water for several minutes. Remove contact lenses

LX - SOFT XTRA

PRECAUTIONS FOR USE

PERSONAL PROTECTIONS:

NA.

VENTILATION:

ADEQUATE VENTILATION IS EXPECTED TO BE SUFFICIENT.

FLAMMABILITY:

NON-FLAMMABLE.

EXPOSURE LIMITS:

NA.

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT:

This product is stable at room temperature if store in closed containers. Store this product in HDPE or polyethylenelined drums. Away from heat sources and sunlight.

SPILL AND DISPOSAL:

Shovel up the spill with absorbent and contain in drum. Flush the affected area with plenty of water.

FIRE / EXPLOSION HAZARD:

None, does not support combustion, use method appropriate for surrounding fire.

OTHER:

NA